

SAFETY DATA SHEET

1. Identification

Product number 21011
Product identifier **SSS Censor Gel Vandal Mark Remover**
Company information Triple S
2 Executive Park Dr
Billerica, MA 01862 United States
Company phone 1-800-323-225; Emergency Phone: 1-888-779-1339
Version # 01
Recommended use CLEANER
Recommended restrictions None known.

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1
Health hazards Skin corrosion/irritation Category 2
Serious eye damage/eye irritation Category 2
Reproductive toxicity Category 1A
Specific target organ toxicity, single exposure Category 3 narcotic effects
Specific target organ toxicity, repeated exposure Category 2
Aspiration hazard Category 1
OSHA defined hazards Not classified.

Label elements



Signal word Danger
Hazard statement Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.
Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.
Response If swallowed: Immediately call a poison center/doctor. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see this label). Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.
Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC) Not classified.
Environmental hazards Hazardous to the aquatic environment, acute hazard Category 2
Hazardous to the aquatic environment, long-term hazard Category 2

Supplemental information

Hazard statement	Toxic to aquatic life. Toxic to aquatic life with long lasting effects.
Prevention	Avoid release to the environment.
Response	Collect spillage.

28.11% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 28.11% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Hazardous components Chemical name	Common name and synonyms	CAS number	%
Toluene		108-88-3	20 - 40
Propane		74-98-6	10 - 20
2-Butoxyethanol		111-76-2	2.5 - 10
Acetone		67-64-1	2.5 - 10
Butane		106-97-8	2.5 - 10
Diethylene Glycol Monobutyl Ether		112-34-5	2.5 - 10
9-Octadecenoic Acid		112-80-1	1 - 2.5
Sodium Hydroxide		1310-73-2	0.1 - 1
Other components below reportable levels			20 - 40

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing. Wash off with soap and plenty of water. If skin irritation occurs: Get medical advice/attention.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis.
Most important symptoms/effects, acute and delayed	Irritation of eyes and mucous membranes. Prolonged exposure may cause chronic effects. May cause drowsiness or dizziness.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Powder. Water. Foam. Carbon dioxide (CO2).
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the MSDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Collect spillage. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the MSDS.
Environmental precautions	Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. Do not get this material in contact with skin. Avoid contact with eyes. Avoid contact during pregnancy/while nursing. Avoid prolonged exposure. Use only in well-ventilated areas. Use personal protective equipment as required. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Do not empty into drains.
Conditions for safe storage, including any incompatibilities	Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the MSDS). Level 2 Aerosol.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	PEL	240 mg/m3
Acetone (CAS 67-64-1)	PEL	50 ppm
		2400 mg/m3
Propane (CAS 74-98-6)	PEL	1000 ppm
		1800 mg/m3
Sodium Hydroxide (CAS 1310-73-2)	PEL	1000 ppm
		2 mg/m3

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm
Acetone (CAS 67-64-1)	STEL	750 ppm
		TWA
Sodium Hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3
Toluene (CAS 108-88-3)	TWA	20 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	24 mg/m3
		5 ppm
Acetone (CAS 67-64-1)	TWA	590 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Butane (CAS 106-97-8)	TWA	250 ppm
		1900 mg/m3
Propane (CAS 74-98-6)	TWA	800 ppm
		1800 mg/m3
Sodium Hydroxide (CAS 1310-73-2)	Ceiling	1000 ppm
Toluene (CAS 108-88-3)	STEL	2 mg/m3
		560 mg/m3
	TWA	150 ppm
		375 mg/m3
		100 ppm

Biological limit values

ACGIH Biological Exposure Indices Components	Value	Determinant	Specimen	Sampling Time
2-Butoxyethanol (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

* - For sampling details, please see the source document.

Exposure guidelines

- US - California OELs: Skin designation
 - 2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.
 - Toluene (CAS 108-88-3) Can be absorbed through the skin.
- US - Minnesota Haz Subs: Skin designation applies
 - 2-Butoxyethanol (CAS 111-76-2) Skin designation applies.
 - Toluene (CAS 108-88-3) Skin designation applies.
- US - Tennessee OELs: Skin designation
 - 2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.
- US NIOSH Pocket Guide to Chemical Hazards: Skin designation
 - 2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.
- US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
 - 2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

Appropriate engineering controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

- Eye/face protection Wear eye/face protection. Wear safety glasses with side shields (or goggles).
- Hand protection Wear protective gloves.
- Other Wear appropriate chemical resistant clothing.
- Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.
- Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

- Appearance Viscous. Liquid.
- Color Tan.
- Form Aerosol.
- Physical state Gas.
- Flash point -156.00 °F (-104.44 °C) Propellant estimated
- Melting point/freezing point Not available.

Odor	Solvent.
pH	12.5 - 13.4 estimated
Solubility(ies)	Not available.
Vapor density	Not available.
Vapor pressure	60 - 75 psig @70F estimated
Viscosity	Not available.
Other information	
Specific gravity	0.751 estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. This product may react with oxidizing agents. Do not mix with other chemicals.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion	May be fatal if swallowed and enters airways.
Inhalation	May be fatal if swallowed and enters airways. Prolonged inhalation may be harmful. Narcotic effects. May cause damage to organs by inhalation.
Skin contact	Causes skin irritation.
	2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

Eye contact Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritant effects.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. Narcotic effects.

Product	Species	Test Results
15 OZ GRAFFITI RMVR PLSTC-SAFE (CAS Mixture)		
Acute		
Oral		
LD50	Rat	9059.501 mg/kg, estimated
Components	Species	Test Results
2-Butoxyethanol (CAS 111-76-2)		
Acute		
Dermal		
LD50	Rabbit	220 mg/kg
Inhalation		
LC50	Mouse	700 mg/l, 7 Hours
	Rat	450 mg/l, 4 Hours
		2.21 mg/l/4h
Oral		
LD50	Guinea pig	1.2 g/kg
	Mouse	1.2 g/kg
	Rabbit	0.32 g/kg
	Rat	470 mg/kg
Other		
LD50	Mouse	1130 mg/kg

Components	Species	Test Results
	Rabbit	280 mg/kg
	Rat	340 mg/kg
9-Octadecenoic Acid (CAS 112-80-1)		
Acute		
Dermal		
LD50	Guinea pig	> 3000 mg/kg
Oral		
LD50	Rat	74 g/kg
Other		
LD50	Mouse	230 mg/kg
	Rat	2.4 mg/kg
Acetone (CAS 67-64-1)		
Acute		
Dermal		
LD50	Rabbit	20000 mg/kg 20 ml/kg
Inhalation		
LC50	Rat	76 mg/l, 4 Hours 50.1 mg/l, 8 Hours
Oral		
LD50	Mouse	3000 mg/kg
	Rabbit	5340 mg/kg
	Rat	5800 mg/kg
Other		
LD50	Mouse	1297 mg/kg
	Rat	5500 mg/kg
Butane (CAS 106-97-8)		
Acute		
Inhalation		
LC50	Mouse	680 mg/l, 2 Hours
	Rat	658 mg/l, 4 Hours
Diethylene Glycol Monobutyl Ether (CAS 112-34-5)		
Acute		
Dermal		
LD50	Rabbit	2700 mg/kg
Oral		
LD50	Guinea pig	2000 mg/kg
	Mouse	2400 mg/kg
	Rabbit	2200 mg/kg
	Rat	4500 mg/kg
Other		
LD50	Mouse	850 mg/kg
	Rat	500 mg/kg
Propane (CAS 74-98-6)		
Acute		
Inhalation		
LC50	Rat	> 1442.847 mg/l, 15 Minutes 658 mg/l/4h
Sodium Hydroxide (CAS 1310-73-2)		
Acute		
Dermal		
LD50	Rat	1350 mg/kg

Components	Species	Test Results
Other LD50	Mouse	40 mg/kg
Toluene (CAS 108-88-3)		
Acute Dermal LD50	Rabbit	12124 mg/kg 14.1 ml/kg
Inhalation LC50	Mouse	5320 mg/l, 8 Hours 400 mg/l, 24 Hours
	Rat	26700 mg/l, 1f <1L: Consumer Commodity Hours 12200 mg/l, 2 Hours 8000 mg/l, 4 Hours
Oral LD50	Rat	2.6 g/kg
Other LD50	Mouse	59 mg/kg
	Rat	1332 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/eye irritation	Causes serious eye irritation.
Respiratory sensitization	Not available.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
IARC Monographs. Overall Evaluation of Carcinogenicity	
2-Butoxyethanol (CAS 111-76-2)	3 Not classifiable as to carcinogenicity to humans.
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.
Reproductive toxicity	May damage fertility or the unborn child.
Specific target organ toxicity - single exposure	Narcotic effects.
Specific target organ toxicity - repeated exposure	Respiratory system. Skin. Kidneys. Central nervous system. Eyes. Liver. May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	May be fatal if swallowed and enters airways.
Chronic effects	Prolonged inhalation may be harmful. May be harmful if absorbed through skin. 2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans. May cause damage to organs through prolonged or repeated exposure.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.

Product	Species	Test Results
15 OZ GRAFFITI RMVR PLSTC-SAFE (CAS Mixture)		
Algae	IC50	Algae 1799.8043 mg/L, 72 Hours, estimated
Crustacea	EC50	Daphnia 31.8818 mg/l, 48 hours, estimated
Fish	LC50	Fish 101.7273 mg/L, 96 Hours, estimated
Components	Species	Test Results
2-Butoxyethanol (CAS 111-76-2)		
Crustacea	EC50	Daphnia 1819 mg/L, 48 Hours

Components	Species	Test Results
Aquatic		
Fish	LC50	Inland silverside (<i>Menidia beryllina</i>) 1250 mg/l, 96 hours
9-Octadecenoic Acid (CAS 112-80-1)		
Aquatic		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 205 mg/l, 96 hours
Acetone (CAS 67-64-1)		
Aquatic		
Crustacea	EC50	Water flea (<i>Daphnia magna</i>) 21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (<i>Oncorhynchus mykiss</i>) 4740 - 6330 mg/l, 96 hours
Diethylene Glycol Monobutyl Ether (CAS 112-34-5)		
Aquatic		
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>) 1300 mg/l, 96 hours
Sodium Hydroxide (CAS 1310-73-2)		
Fish	LC50	Fish 45, 96 Hours
Aquatic		
Crustacea	EC50	Water flea (<i>Ceriodaphnia dubia</i>) 34.59 - 47.13 mg/l, 48 hours
Fish	LC50	Western mosquitofish (<i>Gambusia affinis</i>) 125 mg/l, 96 hours
Toluene (CAS 108-88-3)		
Algae	IC50	Algae 433.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia 7.645 mg/L, 48 Hours
Aquatic		
Crustacea	EC50	Water flea (<i>Daphnia magna</i>) 5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon,silver salmon (<i>Oncorhynchus kisutch</i>) 8.11 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Acetone	-0.24
Diethylene Glycol Monobutyl Ether	0.56
2-Butoxyethanol	0.83
Propane	2.36
Toluene	2.73
Butane	2.89

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

US RCRA Hazardous Waste U List: Reference

Acetone (CAS 67-64-1)	U002
Toluene (CAS 108-88-3)	U220

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	2.1
Subsidiary class(es)	Not available.
Packing group	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Labels required	None
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	2.1
Subsidiary class(es)	-
Packaging group	Not available.
Environmental hazards	Yes
Labels required	2.1
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS, MARINE POLLUTANT
Transport hazard class(es)	2.1
Subsidiary class(es)	-
Packaging group	Not available.
Environmental hazards	
Marine pollutant	Yes
Labels required	2.1
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY


Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

DOT



IATA; IMDG





15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1)	LISTED
Sodium Hydroxide (CAS 1310-73-2)	LISTED
Toluene (CAS 108-88-3)	LISTED

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

SARA 304 Emergency release notification

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories	Immediate Hazard - Yes
	Delayed Hazard - Yes
	Fire Hazard - Yes
	Pressure Hazard - Yes
	Reactivity Hazard - No

SARA 302 Extremely hazardous substance	No
--	----

SARA 311/312 Hazardous chemical	No
---------------------------------	----

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Toluene (CAS 108-88-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA)	Not regulated.
--------------------------------	----------------

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1)	6532
Toluene (CAS 108-88-3)	6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1)	35 % weight/volumn
Toluene (CAS 108-88-3)	35 % weight/volumn

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1)	6532
Toluene (CAS 108-88-3)	594

Food and Drug Administration (FDA)	Not regulated.
------------------------------------	----------------

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8)	500 lbs
Propane (CAS 74-98-6)	500 lbs
Toluene (CAS 108-88-3)	500 lbs

US. Pennsylvania RTK - Hazardous Substances

2-Butoxyethanol (CAS 111-76-2)
9-Octadecenoic Acid (CAS 112-80-1)

Acetone (CAS 67-64-1)
Butane (CAS 106-97-8)
Propane (CAS 74-98-6)
Sodium Hydroxide (CAS 1310-73-2)
Toluene (CAS 108-88-3)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reprod harm.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 03-25-2015

Version # 01

Disclaimer The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.